

MAHARASHTRA POLLUTION CONTROL BOARD

Phone : 24010437/24020781/24014701

Fax : 24023516/24024068/24044531

Email : jdair@mpcb.gov.in

Visit At : <http://mpcb.gov.in>



Kalptaru Point, 2nd, 3rd & 4th Floor,

Opp. Cine Planet,

Near Sion Circle, Sion (E),

Mumbai - 400 022

Red/S.S.I.

Date: 17/08/2020

Consent No: BO/JD (APC)/TB/UAN No. 0000094077/R/CC- 548

Renewal of consent to operate under Section 26 of the Water (Prevention & Control of Pollution) Act, 1974 & under Section 21 of the Air (Prevention & Control of Pollution) Act, 1981 and Authorization / Renewal of Authorization under Rule 5 of the Hazardous & Other Wastes (Management & Transboundary Movement) Rules 2016

[To be referred as Water Act, Air Act and HW (MH & TM) Rules respectively].

CONSENT is hereby granted to

M/s. Pace Autoparts Pvt. Ltd.

Gat No. 1178, Ghotawade Phata, Pirangut,

Tal:- Mulshi, Dist:- Pune, Maharashtra.

located in the area declared under the provisions of the Water Act, Air act and Authorization under the provisions of HW(MH & TM) Rules and amendments thereto subject to the provisions of the Act and the Rules and the Orders that may be made further and subject to the following terms and conditions:

1. The Consent to Operate is granted for a period from 30/04/2020 to 30/04/2021.
2. The Consent is valid for the manufacture of -

Sr. No.	Product Name	Maximum Quantity	UOM
1	Automobile Parts & Accessories with Hard Chrome Plating	70	MT/Month

3. CONDITIONS UNDER WATER ACT:

- (i) The daily quantity of trade effluent from the factory shall not exceed 2.0 CMD.
- (ii) The daily quantity of sewage effluent from the factory shall not exceed 3.0CMD
- (iii) **Trade Effluent: Treatment:** The applicant shall provide comprehensive treatment system consisting of primary / secondary and/or tertiary treatment as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of the treated effluent to the following standards:

1	pH	Between	5.5 to 9.0
---	----	---------	------------

M/s. Pace Autoparts Pvt. Ltd SRO/Pune-II/Red/0000094077

Page 1 of 6

2	Temperature	Should not exceed 5 °C above the ambient Temp of the receiving body	
3	BOD 3 days 27 deg. C.	Not to exceed	30 mg/l.
4	COD	Not to exceed	250 mg/l.
5	Oil & Grease	Not to exceed	10 mg/l.
6	Suspended Solids	Not to exceed	100 mg/l
7	Cyanide (As CN)	Not to exceed	0.2 mg/l
8	Ammonical Nitrogen (As N)	Not to exceed	50 mg/l
9	Total Residual Chlorine (As Cl ₂)	Not to exceed	1.0 mg/l
10	Cadmium (As Cd)	Not to exceed	1.0 mg/l
11	Nickel(As Ni)	Not to exceed	3.0 mg/l
12	Zinc (As Zn)	Not to exceed	5.0 mg/l
13	Chromium as Cr Hexavalent total	Not to exceed	0.1 mg/l
14	Copper (As Cu)	Not to exceed	3.0 mg/l
15	Lead(As Pb)	Not to exceed	0.1 mg/l
16	Iron (As Fe)	Not to exceed	3.0 mg/l
17	Total Metal	Not to exceed	10.0 mg/l

(iv) **Trade Effluent Disposal:** The treated effluent shall be 100% recycling tread effluent in process to achieve Zero Liquid Discharge. In no case, at any time effluent shall finds its way to any water body directly or indirectly.

(v) **Sewage Effluent Treatment:** The applicant shall provide comprehensive treatment system as is warranted with reference to influent quality and operate and maintain the same continuously so as to achieve the quality of treated effluent to the following standards.

(1)	Suspended Solids	Not to exceed	100	mg/l.
(2)	BOD 3 days 27° C.	Not to exceed	10	mg/l.

(vi) **Sewage Effluent Disposal:** The treated domestic effluent shall be soaked in a soak pit, which shall be cleaned periodically. Overflow, if any, shall be used on land for gardening / plantation only.

(vii) **Non-Hazardous Solid Wastes:** Nil

Sr. No.	Type Of Waste	Quantity	Treatment	Disposal
1	MS Scrap	25 Kg/M	Recycling	Send to MPCB authorized recycler

(viii) **Other Conditions:** Industry should monitor effluent quality regularly.

4. The applicant shall comply with the provisions of the Water (Prevention & Control of Pollution) Cess Act, 1977 (to be referred as Cess Act) and amendment Rules, 2003 there under

The daily water consumption for the following categories is as under:

(i) Domestic purpose ... 2.5 CMD

M/s. Pace Autoparts Pvt. Ltd SRO/Pune-II/Red/0000094077

(ii) Industrial Processing	...	4.0 CMD
(iii) Industrial Cooling. Boiler	...	0.0 CMD
(iv) Agriculture / Gardening	...	--- CMD

The applicant shall regularly submit to the Board the returns of water consumption in the prescribed form and pay the Cess as specified under Section 3 of the said Act.

5. CONDITIONS UNDER AIR ACT :

- (i) The applicant shall install a comprehensive control system consisting of control equipments as is warranted with reference to generation of emission and operate and maintain the same continuously so as to achieve the level of pollutants to the following standards:

A. Control Equipment:

- I. Dust Collection system of sufficient capacity provided to source of SPM/TPM shall be operate and maintain regularly.
- II. Wet scrubber of sufficient capacity provided to plating section & acid pickling shall be operated properly and maintain regularly.
- III. There shall not be any secondary (fugitive) emissions.

B. Condition for DG set

- a. Noise from the D.G. Set should be controlled by providing an acoustic enclosure or by treating the room acoustically.
- b. Industry should provide acoustic enclosure for control of noise. The acoustic enclosure/ acoustic treatment of the room should be designed for minimum 25 dB (A) insertion loss or for meeting the ambient noise standards, whichever is on higher side. A suitable exhaust muffler with insertion loss of 25 dB (A) shall also be provided. The measurement of insertion loss will be done at different points at 0.5 meters from acoustic enclosure/room and then average.
- c. Industry should make efforts to bring down noise level due to DG set, outside industrial premises, within ambient noise requirements by proper siting and control measures.
- d. Installation of DG Set must be strictly in compliance with recommendations of DG Set manufacturer.
- e. A proper routine and preventive maintenance procedure for DG set should be set and followed in consultation with the DG manufacturer which would help to prevent noise levels of DG set from deteriorating with use
- f. D.G. Set shall be operated only in case of power failure.
- g. The applicant should not cause any nuisance in the surrounding area due to operation of D.G. Set.
- h. The applicant shall comply with the notification of MoEF dated 17.05.2002 regarding noise limit for generator sets run with diesel

C. Standards for Emissions of Air Pollutants:

(i) SPM/TPM	Not to exceed	100 mg/Nm ³
(ii) SO ₂	Not to exceed	--- Kg / Day.
(iii) Acid Mist	Not to exceed	35 mg/Nm ³

6. Fuel consumption and Stack Details:

(i) The applicant shall observe the following fuel pattern:-

Sr. No.	Type Of Fuel	Quantity	UOM
--	--	--	--

(ii) The applicant shall erect the chimney(s) of the following specifications:-

Sr. No.	Chimney Attached To	Height in Mtrs.
1.	Hard Chrome plating (Wet Scrubber)	11.00
2.	Acid bath (Wet Scrubber)	11.00

(iii) The applicant shall provide ports in the chimney/(s) and facilities such as ladder, platform etc. for monitoring the air emissions and the same shall be open for inspection to/and for use of the Board's Staff. The chimney(s) vents attached to various sources of emission shall be designated by numbers such as S-1, S-2, etc. and these shall be painted/ displayed to facilitate identification.

(iv) The industry shall take adequate measures for control of noise levels from its own sources within the premises so as to maintain ambient air quality standard in respect of noise to less than 75 dB(A) during day time and 70 dB(A) during night time. Day time is reckoned in between 6 a.m. and 10 p.m. and night time is reckoned between 10 p.m. and 6 a.m.

(v) Other Conditions:

- 1) The industry should not cause any nuisance in surrounding area.
- 2) The industry should monitor stack emissions and ambient air quality regularly.

7. CONDITIONS UNDER HAZARDOUS & OTHER WASTES
(MANAGEMENT & TRANSBOUNDRY MOVEMENT) RULES, 2016:

(i) The industry shall handle hazardous wastes as specified below:

Sr. No.	Type Of Waste	Quantity	Treatment	Disposal
1.	35.3 Chemical Sludge generating from Waste Water Treatment	100 kg/M	Secured land filling after treatment	CHWTSDF
2.	12.2 Spent acid and alkali	---	Reprocessing	Send to MPCB authorized Spent acid regeneration plant

8. Whenever due to any accident or gas leakage or other unforeseen act or even, such emission occur or is apprehended to occur in excess of standards laid down, such information shall be forthwith Reported to Collector, Directorate of industry, Safety and Health, Police Station, fire Brigade, Directorate of Health services, Department of Explosives, Board and local Body the production process should be stopped by taking all necessary safety measures. Industry shall also monitor the emission and ensure that

M/s. Pace Autoparts Pvt. Ltd SRO/Pune-II/Red/0000094077

Page 4 of 6

the emission do not cause any harm or nuisance in the surrounding. The industry should not restart the process without permission of the Board and other statutory organization as require under the law.

9. Industry shall comply with following general conditions:

- i. The applicant shall maintain good housekeeping and take adequate measures for control of pollution from all sources so as not to cause nuisance to surrounding area / inhabitants.
- ii. The applicant shall bring minimum 33% of the available open land under green coverage/ tree plantation.
- iii. Solid waste – The non hazardous solid waste arising in the factory premises, sweepings, etc., be disposed of scientifically so as not to cause any nuisance / pollution. The applicant shall take necessary permissions from civic authorities for disposal to dumping ground.
- iv. The applicant shall provide for an alternate electric power source sufficient to operate all pollution control facilities installed by he applicant to maintain compliance with the terms and conditions of the consent. In the absence, the applicant shall stop, reduce or otherwise, control production to abide by terms & conditions of this consent regarding pollution levels.
- v. The applicant shall not change or alter quantity, quality, the rate of discharge, temperature or the mode of the effluent / emissions or hazardous wastes or control equipments provided for without previous written permission of the Board.
- vi. The applicant shall provide facility for collection of environmental samples and samples of trade and sewage effluents, air emissions and hazardous wastes to the Board staff at the terminal or designated points and shall pay to the Board for the services rendered in this behalf.
- vii. The applicant shall obtain consent to operate from MPC Board before commencement of production.
- viii. As inspection book shall be opened and made available to the Board's officers during their visit to the applicant.
- ix. The applicant shall install a separate electric meter showing the consumption of energy for operation of domestic and industrial effluent treatment plants and air pollution control system. A register showing consumption of chemicals used for treatment shall be maintained.
- x. Separate drainage system shall be provided for collection of trade and sewage effluents. Terminal manholes shall be provided at the end of collection system with arrangement for measuring the flow. No effluent shall be admitted in the pipes / sewers down- stream of the terminal manholes. No effluent shall find its way other than in designed and provided collection System.
- xi. Neither storm water nor discharge from other premises shall be allowed to mix with the effluents from the factory.
- xii. The industry shall achieve the National Ambient Air Quality standards prescribed vide Government of India, Notification dt. 16.11.2009 as amended.


10. The Board reserves the rights to add/amend/revoke any condition in this consent and the same shall be binding on the applicant.

M/s. Pace Autoparts Pvt. Ltd SRO/Pune-II/Red/0000094077

Page 5 of 6

12. The industry shall not treat spend acid in Effluent treatment plant.
13. The industry shall send spend acid to MPCB authorised recycler and submit monthly manifest regarding sending of spent acid to authorised recycler to Regional Officer, MPCB.
14. Industry shall upgrade existing Effluent Treatment Plant to achieve Zero Liquid Discharge.
15. The industry shall obtain Central Ground Water Authority NOC for utilization of ground water within 3 month form date of this consent granted.
16. The industry shall submit Bank Guarantee of Rs. 1,00,000/- upto 31/08/2021 towards compliance of consent conditions and submit to Regional Office Pune within 15 days time. If fail to submit consent will be revoke automatically after 30 days form grant of consent.
17. The total Capital investment of industry is Rs. 1.05 Cr.

For and On Behalf of the
Maharashtra Pollution Control Board,


(Dr. V. M. Motghare)
Joint Director (Air Pollution Control)

To,
M/s. Pace Autoparts Pvt. Ltd.
Gat No. 1178, Ghotawade Phata, Pirangut,
Tal:- Mulshi, Dist:- Pune, Maharashtra.

Copy to:

- a. RO- Pune /SRO-Pune II, MPCB, Pune: Directed to obtain Bank Guarantee as per consent conditions and submit compliance report within month.
- b. CAO/Cess Branch/Master File

Received Online Consent fee of -

Sr. No.	Amount(Rs.)	DR No.	Date
1	Rs. 45,000/-	MPCB-DR-0778	07/07/2020

Rs. 30,000/- balance with Board will be adjusted during next renewa.