

PREVENTIVE MAINTENANCE CHECK LIST FOR DIES

Format No. :- ASM/F/TR/04 Rev. No. :- 07 Eff. Date :- 10/07/2022

SCHEDULE

Preventive maintenance to be done

Note - Part Name, Die no & Date must to maintained on report Part Name - De No - PM Date - Routine / Preventive Maint. Check List 1 Open the Die & dean properly to remove the rust, dirk & dust 2 Leakage of Cooling pipe to be checked & Replace if required	1. First 5000 shots 2. Between Every 20000 Shots to 25000 Shots			
Part Name :- PM Date :- PM Date :- PM Date :- Routine / Preventive Maint. Chack List 1	Note :- Part Name, Die no.& Date must to maintained on report			
1 Open the Dis & clean properly to remove the rust, dir & dust 2 Leakage of Cooling pipe to be checked & Replace if required 3 Send to cilioward in their forming pin & Harriden Pin to be used. 4 4 Bush Fitting Pins to be check for bond & replace if required. 5 Gap not allowed helder forming pins & Harriden Pin to be used. 4 6 Cleaning of silcos & stoppers to be done 7 Blue matching to be done of inserts, sprue bush, Diffuser & punches etc. 8 Polishing to be done 9 To check & repair the die block, ejector box, mounting surface, clamp slots, guide pins. 10 Guide pillar, A bush to be checked & repair if req. & changed every 25000 shots. 11 Sprue bush & diffuser to be checked & repair if required every 45000 shots. 12 Stress refleving & nitriding to be done every 40000 shots 13 Check the Gate erosion, Depth & Width 14 Check the Gate erosion, Depth & Width 15 Check the Haat check marks, Crack ,dent & Damage 16 EDM Marks to be checked 17 Check the NG Point as per Last Shot Report (Die /Tool Rectification) 18 Pillars to be cheked for bending before loading 19 Check tall ejector pin head & if required, to be changed & ensure the height also 19 Ejector pins hole to be lubricated & Checked for Pillar (Pilly not allowed) 20 Ejector pins hole to be lubricated & Checked for Pillar (Pilly not allowed) 21 Ejector pins hole to be lubricated & Checked for Pillar (Pilly not allowed) 22 Ejector pins hole to be lubricated & Checked for Pillar (Pilly not allowed) 23 Engraving must be clear & visible. 24 Engraving height //Victin to be checked at customer end during Dovelopment //New 24 Engraving height //Victin to be checked at customer end during Dovelopment //New 25 Domment If Any:-	Part Name :			
Leakage of Cooling pipe to be checked & Replace if required Hole forming pins replaced if required,		Routine / Preventive Maint. Che	ck List	
Bend not allowed in Hole forming pins explaced if required. Bend not allowed between hole forming pins & Harden Pin to be used. Gap not allowed between hole forming pins & Harden Pin to be used. Gisening of silides & stoppers to be done Blue matching to be done of inserts, sprue bush, Diffuser & punches etc. Polishing to be done To check & repair the die block, ejector box, mounting surface, clamp slots, guide pins Guide pillar & bush to be checked & repair if req. & changed every 25000 shots Sprue bush & diffuser to be checked & repair if required every 45000 shots. Stress relieving & nitriding to be done every 40000 shots. Stress relieving & nitriding to be done every 40000 shots. Check the Gate crosion, Depth & Width Check the Heat check marks, Crack, dent & Damage EDM Marks to be checked Attend the NG Point as per Last Shot Report (Die /Tool Rectification) Check the hydraulic cylinder & accumalator Billars to be checked for bending before loading Check all ejector pin hole to be lubricated & Checked for Play (Play not allowed) Ejector pins hole to be checked of checked of replay (Play not allowed) Ejector pins hole to be checked of checked of replay (Play not allowed) Ejector pins hole to be checked of checked of relay (Play not allowed) Ejector pins hole to be checked of checked of play (Play not allowed) Ejector pins hole to be checked before die loading Tile Bar rod Condition to be checked at customer and during Doveloipment /fday bile Comment If Any:	1	Open the Die & clean properly to remove the rust, dirt & dust		
Bend not allowed in Hole forming pin & Harden Pin to be used. Bush Fitting Pins to be check for bend & replace if required. Gap not allowed between hole forming pins. Cleaning of slides & stoppers to be done Blue matching to be done of inserts, sprue bush, Diffuser & punches etc. Polishing to be done To check & repair the die block, ejector box, mounting surface, clamp slots, guide pins. Guide pillar, & bush to be checked & repair if req. & changed every 25000 shots Sprue bush & diffuser to be checked & repair if req. & changed every 45000 shots. Stress relieving & nitriding to be done every 40000 shots Check the Gate erosion, Depth & Width Check the Heat check marks, Crack, dent & Damage EDM Marks to be checked Attend the NR Point as per Last Shot Report (Die /Tool Rectification) Check the hydraulic cylinder & accumalator Pillars to be checked for bending before loading By Check all ejector pin head & if required, to be changed & ensure the height also Ejector pins hole to be lubricated & Checked for Play (Play not allowed) Ejector pins hole to be checked before die loading Engraving must be clear & visible. Last Engraving height NVidth to be checked at customer end during Dovelopment Reave Die Comment If Any:-		4		
Gap not allowed between hole forming pins Cleaning of sildes & stoppers to be done Place matching to be done of inserts, sprue bush, Diffuser & punches etc. Polishing to be done Guide pillar, & bush to be checked & repair if req. & changed every 25000 shots Sprue bush & diffuser to be checked & repair if req. & changed every 25000 shots Stress relieving & nitriding to be done every 40000 shots Check the Gate erosion, Depth & Width Check the Heat check marks, Crack .dent & Damage Both Marks to be checked Attend the NG Point as per Last Shot Report (Die /Tool Rectification) Check the Hydraulic cylinder & accumalator Relians to be checked for bending before loading Check all ejector pin head & if required , to be changed & ensure the height also Ejector pins hole to be lubricated & Checked for Play (Play not allowed) Ejector pias hole to be checked before die loading Engraving must be clear & visible. Engraving must be clear & visible. Engraving height /Width to be checked at customer end during Doveloipment / New Die Comment If Any:- Initial Effective Date: 13.09.18	3			
6 Cleaning of silides & stoppers to be done 7 Blue matching to be done of inserts, sprue bush, Diffuser & punches etc. 8 Polishing to be done 9 To check & repair the die block, ejector box, mounting surface, clamp slots, guide pins 10 Guide pillar & bush to be checked & repair if req. & changed every 25000 shots 11 Sprue bush & diffuser to be checked & repair if required every 45000 shots. 12 Stress relieving & nitriding to be done every 40000 shots 13 Check the Gate erosion, Depth & Wilder 14 Check the Heat check marks, Crack ,dent & Damage 15 EDM Marks to be checked 16 Attend the NG Point as per Last Shot Report (Die /Tool Rectification) 17 Check the hydraulic cylinder & accumalator 18 Pillars to be checked for bending before loading 19 Check all ejector pin head & if required , to be changed & ensure the height also 20 Ejector piate to be check for depression (deformation) during preventive maintenance 21 Tie Bar rod Condition to be checked at customer end during Doveloipment Aeve Die 22 Engraving must be clear & visible. 23 Engraving must be clear & visible. 24 Engraving height Width to be checked at customer end during Doveloipment Aeve Die 25 Comment If Any:-	4	Bush Fitting Pins to be check for bend & replace if required.		
Blue matching to be done of inserts, sprue bush, Diffuser & punches etc. Polishing to be done To check & repair the die block, ejector box, mounting surface, clamp slots, guide pins Guide pillar & bush to be checked & repair if req. & changed every 25000 shots Sprue bush & diffuser to be checked & repair if required every 45000 shots. Stress relieving & nitriding to be done every 40000 shots Check the Gate erosion, Depth & Width Check the Heat check marks, Crack ,dent & Damage EDM Marks to be checked Attend the NO Point as per Last Shot Report (Die /Tool Rectification) Check the hydraulic cylinder & accumalator Pillars to be checked for bending before loading Check all ejector pin head & if required , to be changed & ensure the height also Die Ejector pins hole to be lubricated & Checked for Play (Play not allowed) Ejector pilate to be check for depression (deformation) during preventive maintenance Tie Bar rod Condition to be checked before die loading Engraving must be clear & visible. Engraving must be clear & visible. Initial Effective Date : 13.09.18	5	Gap not allowed between hole forming pins 2		
Polishing to be done To check & repair the die block, ejector box, mounting surface, clamp slots, guide pill Cuide pillar & bush to be checked & repair if req. & changed every 25000 shots Stress relieving & nitriding to be done every 40000 shots Check the Gate erosion, Depth & Width Check the Heat check marks, Crack ,dent & Damage EDM Marks to be checked Attend the NB Point as per Last Shot Report (Die /Tool Rectification) Check the hydraulic cylinder & accumalator Pillar to be checked for bending before loading Check all ejector pin head & if required , to be changed & ensure the height also Ejector pins hole to be lubricated & Checked for Play (Play not allowed) Ejector plate to be check for depression (deformation) during preventive maintenance Te Bar rod Condition to be checked at customer end during Doveloipment New Die Comment If Ary :- Initial Effective Date : 13.09.18	6	Cleaning of slides & stoppers to be done		
To check & repair the die block, ejector box, mounting surface, clamp slots, guide pins Guide pillar bush to be checked & repair if req. & changed every 25000 shots Stress relieving & nitriding to be done every 40000 shots Check the Gate erosion, Depth & Width Check the Heat check marks, Crack, dent & Damage EDM Marks to be checked Attend the NG Point as per Last Shot Report (Die /Tool Rectification) Check the hydraulic cylinder & accumalator Pillars to be checked for bending before loading Check all ejector pins hole to be lubricated & Checked for Play (Play not allowed) Ejector pins hole to be checked for depression (deformation) during preventive maintenance Ejector plate to be checked before die loading Engraving must be clear & visible. Engraving must be clear & visible. Engraving height /Width to be checked at customer end during Doveloipment / New Die Linitial Effective Date: 13.09.18	7	Blue matching to be done of inserts, sprue bush, Diffuser & punches etc.		
pins Guide pillar & bush to be checked & repair if req. & changed every 25000 shots Sprue bush & diffuser to be checked & repair if required every 45000 shots. Stress relieving & nitriding to be done every 40000 shots Check the Gate erosion, Depth & Width Check the Heat check marks, Crack ,dent & Damage EDM Marks to be checked Attend the NG Point as per Last Shot Report (Die /Tool Rectification) Check the hydraulic cylinder & accumalator Pillars to be checked for bending before loading Check all ejector pin head & if required , to be changed & ensure the height also Ejector pins hole to be lubricated & Checked for Play (Play not allowed) Ejector pins hole to be lubricated & Checked for Play (Play not allowed) Ejector pins must be clear & visible. Engraving must be clear & visible. Engraving height /Width to be checked at customer end during Doveloipment / New Die Comment If Any:- Initial Effective Date: 13.09.18	8	Polishing to be done		
11 Sprue bush & diffuser to be checked & repair if required every 45000 shots. 12 Stress relieving & nitriding to be done every 40000 shots 13 Check the Gate erosion, Depth & Width 14 Check the Heat check marks, Crack ,dent & Damage 15 EDM Marks to be checked 16 Attend the NC Point as per Last Shot Report (Die /Tool Rectification) 17 Check the hydraulic cylinder & accumalator 18 Pillars to be cheked for bending before loading 19 Check all ejector pin head & if required , to be changed & ensure the height also 20 Ejector pins hole to be lubricated & Checked for Play (Play not allowed) 21 Ejector plate to be check for depression (deformation) during preventive maintenance 22 Tie Bar rod Condition to be checked before die loading 23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment /New Die Comment If Any:-	9			
12 Stress relieving & nitriding to be done every 40000 shots 13 Check the Gate erosion, Depth & Width 14 Check the Heat check marks, Crack ,dent & Damage 15 EDM Marks to be checked 16 Attend the NG Point as per Last Shot Report (Die /Tool Rectification) 17 Check the hydraulic cylinder & accumalator 18 Pillars to be cheked for bending before loading 19 Check all ejector pin head & if required , to be changed & ensure the height also 20 Ejector pins hole to be lubricated & Checked for Play (Play not allowed) 21 Ejector plate to be check for depression (deformation) during preventive maintenance 22 Tie Bar rod Condition to be checked before die loading 23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment New Die Comment If Any:-	10	. / \		
Comment If Any:- Check the Gate erosion, Depth & Width Check the Heat check marks, Crack ,dent & Damage 15 EDM Marks to be checked 16 Attend the NG Point as per Last Shot Report (Die /Tool Rectification) 17 Check the hydraulic cylinder & accumalator 18 Pillars to be cheked for bending before loading 19 Check all ejector pin head & if required , to be changed & ensure the height also 20 Ejector pins hole to be lubricated & Checked for Play (Play not allowed) 21 Ejector plate to be check for depression (deformation) during preventive maintenance 22 Tie Bar rod Condition to be checked before die loading 23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Doveloipment for beautiful and the checked at customer end during Dove	11	Sprue bush & diffuser to be checked & repair if required every 45000 shots.		
14 Check the Heat check marks, Crack ,dent & Damage 15 EDM Marks to be checked 16 Attend the NG Point as per Last Shot Report (Die /Tool Rectification) 17 Check the hydraulic cylinder & accumalator 18 Pillars to be checked for bending before loading 19 Check all ejector pin head & if required , to be changed & ensure the height also 20 Ejector pins hole to be lubricated & Checked for Play (Play not allowed) 21 Ejector plate to be check for depression (deformation) during preventive maintenance 22 Tie Bar rod Condition to be checked before die loading 23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment by Die Comment If Any:- Initial Effective Date: 13.09.18	12	Stress relieving & nitriding to be done every 40000 shots		
15 EDM Marks to be checked 16 Attend the NG Point as per Last Shot Report (Die /Tool Rectification) 17 Check the hydraulic cylinder & accumalator 18 Pillars to be cheked for bending before loading 19 Check all ejector pin head & if required, to be changed & ensure the height also 20 Ejector pins hole to be lubricated & Checked for Play (Play not allowed) 21 Ejector plate to be check for depression (deformation) during preventive maintenance 22 Tie Bar rod Condition to be checked before die loading 23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment by Die Comment If Any:- Initial Effective Date: 13.09.18	13	Check the Gate erosion, Depth & Width		
Attend the NG Point as per Last Shot Report (Die /Tool Rectification) 17 Check the hydraulic cylinder & accumalator 18 Pillars to be cheked for bending before loading 19 Check all ejector pin head & if required , to be changed & ensure the height also 20 Ejector pins hole to be lubricated & Checked for Play (Play not allowed) 21 Ejector plate to be check for depression (deformation) during preventive maintenance 22 Tie Bar rod Condition to be checked before die loading 23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment New Die Die Comment If Any:-	14	Check the Heat check marks, Crack ,dent & Damage		
17 Check the hydraulic cylinder & accumalator 18 Pillars to be cheked for bending before loading 19 Check all ejector pin head & if required, to be changed & ensure the height also 20 Ejector pins hole to be lubricated & Checked for Play (Play not allowed) 21 Ejector plate to be check for depression (deformation) during preventive maintenance 22 Tie Bar rod Condition to be checked before die loading 23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment for the bilding Die Comment If Any:-	15	EDM Marks to be checked		
Pillars to be cheked for bending before loading 19 Check all ejector pin head & if required , to be changed & ensure the height also 20 Ejector pins hole to be lubricated & Checked for Play (Play not allowed) 21 Ejector plate to be check for depression (deformation) during preventive maintenance 22 Tie Bar rod Condition to be checked before die loading 23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment / New Die Comment If Any:- Initial Effective Date: 13.09.18	16	Attend the NG Point as per Last Shot Report (Die /Tool Rectification)		
Check all ejector pin head & if required , to be changed & ensure the height also Ejector pins hole to be lubricated & Checked for Play (Play not allowed) Ejector plate to be check for depression (deformation) during preventive maintenance Tie Bar rod Condition to be checked before die loading Engraving must be clear & visible. Engraving height /Width to be checked at customer end during Doveloipment for being b	17	Check the hydraulic cylinder & accumalator		
20 Ejector pins hole to be lubricated & Checked for Play (Play not allowed) 21 Ejector plate to be check for depression (deformation) during preventive maintenance 22 Tie Bar rod Condition to be checked before die loading 23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment Naw Die Comment If Any:- Initial Effective Date: 13.09.18	18	Pillars to be cheked for bending before loading		
Ejector plate to be check for depression (deformation) during preventive maintenance Tie Bar rod Condition to be checked before die loading Engraving must be clear & visible. Engraving height /Width to be checked at customer end during Doveloipment /New Die Comment If Any :- Initial Effective Date : 13.09.18	19	Check all ejector pin head & if required, to be changed & ensure the height also		
maintenance Tie Bar rod Condition to be checked before die loading Engraving must be clear & visible. Engraving height /Width to be checked at customer end during Doveloipment flaw Die Comment If Any:- Initial Effective Date: 13.09.18	20	Ejector pins hole to be lubricated & Checked for Play (Play not allowed)		
23 Engraving must be clear & visible. 24 Engraving height /Width to be checked at customer end during Doveloipment / New Die Comment If Any:- Initial Effective Date: 13.09.18	21			
24 Engraving height /Width to be checked at customer end during Doveloipment New Die Comment If Any:- Initial Effective Date: 13.09.18	22	Tie Bar rod Condition to be checked before die loading		
Comment If Any :- Initial Effective Date : 13.09.18				
Initial Effective Date : 13.09.18	24			
	Comment If Any :-			
CHECKED BY: VERIFIED BY:	Initial Effect	ive Date: 13.09.18		
	СН	ECKED BY:	VERIFIED BY:	